



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT (FR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 VOLTS

| Size (sq.mm.) | FR | | | | | |
|---------------|----------|---------------|-------------------------|---------------|---------------|---------------|
| | 90 Mtrs. | Coils Per Box | 180 Mtrs. (Box Packing) | Coils Per Box | 300/200 Mtrs. | Coils Per Box |
| 0.75 | 810 | 28 | | | 2700 | 10 |
| 1 | 1055 | 24 | 2110 | 12 | 3515 | 8 |
| 1.5 | 1570 | 16 | 3140 | 10 | 5235 | 6 |
| 2.5 | 2525 | 12 | 5050 | 6 | 8415 | 4 |
| 4 | 3735 | 8 | 7470 | 4 | 8300 | 4 |
| 6 | 5540 | 6 | 11080 | 3 | 12310 | 3 |
| 10 | 9750 | 1 | | | 21670 | 1 |
| 16 | 15600 | 1 | | | 34665 | 1 |

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES – FLAME RETARDANT LOW SMOKE (FRLSH) /FLAME RETARDANT ZERO HALOGEN (FRZH) / LOW SMOKE ZERO HALOGEN (LSZH) / HALOGEN FREE FLAME RETARDANT (HFFR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 VOLTS

| Size (sq.mm.) | FRLS | | | | FRZH/LSZH/HFFR | |
|---------------|-------------------------|---------------|---------------|---------------|----------------|---------------|
| | 180 Mtrs. (Box Packing) | Coils Per Box | 300/200 Mtrs. | Coils Per Box | 300/200 Mtrs. | Coils Per Box |
| 0.75 | | | 2850 | 10 | 3190 | 10 |
| 1 | 2185 | 12 | 3650 | 8 | 3940 | 8 |
| 1.5 | 3305 | 10 | 5510 | 6 | 6105 | 6 |
| 2.5 | 5315 | 6 | 8855 | 4 | 10040 | 4 |
| 4 | 7850 | 4 | 8720 | 4 | 9750 | 4 |
| 6 | 11600 | 3 | 12890 | 3 | 14235 | 3 |
| 10 | | | 22815 | 1 | 25060 | 1 |
| 16 | | | 36565 | 1 | 39975 | 1 |

Notes

- Excise Duty, VAT, Entry Tax, Octroi/ LBT and any other tax/levy will be charged extra, as per actuals.
- This Price List is subject to change without notice.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB INDUSTRIAL JELLY FLOODED COAXIAL CABLES

Polycab Gas Injected Physical Polyethylene Foam Insulation with Laminated Aluminium Tape and Aluminium Wire Braid, Jelly Flooded PVC Black Jacketed Industrial Coaxial Cables.

| Size | 100m Unarmoured | 305m Unarmoured | 1000m Armoured |
|-----------|-----------------|-----------------|----------------|
| RG - 59 | 1870 | 5215 | 76050 |
| RG - 6 | 2430 | 7410 | 78975 |
| RG - 11 | 5040 | 15405 | 121875 |
| RG-6 CCS | 1540 | 4710 | 71175 |
| RG-11 CCS | 3090 | 9420 | |

POLYCAB LAN (COMPUTER) CABLES

Polycab 4 Pair Unshielded Twisted Pair (UTP) LAN (Computer) Cables

Polycab 4 Pair Shielded Twisted Pair (STP) LAN (Computer) Cables

| | Unarmoured Rate per 305 m | Armoured- Rate per 100m | STP- Rate per 305m | Armoured – Rate per 100m |
|---------|---------------------------|-------------------------|--------------------|--------------------------|
| CAT 5 E | 8735 | 6810 | 11325 | 8095 |
| CAT 6 | 10415 | 7805 | 13205 | 9265 |



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB INDUSTRIAL TELEPHONE (SWITCHBOARD)CABLES

Polycab High Conductivity Solid Annealed Bare Copper industrial Telephone (Switchboard) Cables with High Density Polyethylene Insulation, Paired, Polyester and Sheathed with High Oxygen Index, Fire Retardant, PVC Compound, Grey Outer Sheath generally conforming ITD Specification

| No. of Pairs & Size | | | |
|---------------------|--------|--------|----------------|
| | 0.4 mm | 0.5 mm | Master Packing |
| 1 Pair | 650 | 780 | 20 |
| 2 Pair | 1035 | 1365 | 20 |
| 3 Pair | 1520 | 1990 | 16 |
| 4 Pair | 1950 | 2615 | 12 |
| 5 Pair | 2440 | 3265 | 8 |
| 10 Pair | | 6240 | 1 |
| 20 Pair | | 12000 | 1 |
| 50 Pair | | 33200 | 1 |
| 100 Pair | | 63400 | 1 |

ARMOURED TELEPHONE CABLES

| No. of Pairs | Rate / 100m (0.5sqmm) | Master Packing 0.5 mm |
|--------------|-----------------------|------------------------------|
| 2 Pair | 4485 | 0 Drums/Coils as required |
| 5 Pair | 7400 | 0 Drums/Coils as required |
| 10 Pair | 11100 | 0 Drums/Coils as required |
| 15 Pair | 15200 | 0 Drums/Coils as required |
| 20 Pair | 18700 | 0 Drums/Coils as required |
| 50 Pair | 44900 | 0 Drums/Coils as required |
| 100 Pair | 82200 | 0 Drums/Coils as required |

POLYCAB IND. 3C FLAT SUBMERSIBLE CABLES

Polycab PVC Insulated and PVC Sheathed Industrial 3 Core Flat Submersible Cable with Bare Bunched Copper Conductor for Submersible Pump Motors with Voltage Grade upto 1100 Volts as per IS:694/1990

| Nominal Area of Conductor (sq mm) | Number/ Nom. Dia of Cables (No./dia mm) | Rate per 100m (Rs) |
|-----------------------------------|---|--------------------|
| 1.5 | 22/.3 | 6500 |
| 2.5 | 36/.3 | 10100 |
| 4 | 56/.3 | 14900 |

Polycab Special PVC Insulated & PVC Sheathed Industrial 3 Core Flat Submersible Cables with Bare Bunched Copper Conductor for Submersible Pump Motors with Voltage Grade Upto 1100 Volts generally conforming to IS 694/1990.

| Nominal Area of Conductor (sq mm) | Number/ Nom. Dia of Cables (No./dia mm) | Rate per 100m (Rs) |
|-----------------------------------|---|--------------------|
| 6 | 84/0.3 | 21900 |
| 10 | 80/0.4 | 37400 |
| 16 | 126/0.4 | 59900 |
| 25 | 196/0.4 | 95900 |
| 35 | 276/.4 | 134400 |
| 50 | 396/.4 | 192300 |
| 70 | 354/.5 | 267600 |
| 95 | | 345800 |
| 120 | | 442100 |
| 150 | | 550900 |

Notes :

1) The above cables are supplied in 500/1000m drums.

2) Polycab Three Core Flat Submersible Cables

Insulated & Sheathed with XLPE can be supplied at

the same rates as given above.



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

Polycab PVC Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:1990 with Flexible Bright Annealed Copper Conductor for Voltage Grade upto 1100 Volts

Polycab PVC Insulated and PVC Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Cables for Voltage Grade upto 1100 Volts as per IS: 694:1990

| Nominal Area of Conductor (sq mm) | Number/ Nom. Dia of Conductor (No./dia mm) | Current Carrying Capacity (Amps) | (Rate/100m) | | | | | | | |
|-----------------------------------|--|----------------------------------|-------------|---------|---------|---------|---------|--------------------|---------|--------|
| | | | Single Core | Packing | 2 Core | 3 Core | 4 Core | 2 - 4 Core Packing | 5 Core | 6 Core |
| 0.5 | 16/.2 | 5 | 625 | 25 | 1970 | 2650 | 3410 | 4 | 4330 | 5130 |
| 0.75 | 24/.2 | 8 | 880 | 25 | 2625 | 3570 | 4435 | 4 | 6055 | 7400 |
| 1 | 32/.2 | 13 | 1150 | 20 | 3130 | 4310 | 5625 | 4 | 8000 | 9350 |
| 1.5 | 30/.25 | 17 | 1670 | 16 | 4235 | 5940 | 7880 | 4 | 10400 | 12700 |
| 2.5 | 50/.25 | 24 | 2750 | 12 | 6750 | 9500 | 12600 | 3 | 17100 | 20700 |
| 4 | 56/.3 | 30 | 4310 | 8 | 10000 | 14200 | 18600 | 1 | 26000 | 32800 |
| 6 | 84/.3 | 38 | 6240 | 6 | 15000 | 21600 | 28100 | -- | 40300 | 48200 |
| 10 | 80/.4 | 52 | 10800 | 1 | 25500 | 36800 | 47900 | -- | 68500 | -- |
| 16 | 126/.4 | 70 | 17500 | 1 | 40700 | 58600 | 77100 | -- | 106800 | -- |
| 25 | 196/.4 | 88 | 27600 | 1 | 77000 | 104700 | 137700 | -- | 181100 | -- |
| 35 | 276/.4 | 110 | 38100 | 1 | 105100 | 145000 | 190400 | -- | 250100 | -- |
| 50 | 396/.4 | 145 | 54400 | 1 | 152200 | 206600 | 276500 | -- | 362600 | -- |
| 70 | 354/.5 | 215 | 75600 | 1 | 216800 | 297100 | 386300 | | 505800 | |
| 95 | 484/.5 | 260 | 105800 | 1 | 292800 | 407100 | 537500 | | 698000 | |
| 120 | 608/.5 | 305 | 135000 | 1 | 370700 | 516600 | 693000 | | 906600 | |
| 150 | 750/.5 | 355 | 168900 | 1 | 462600 | 641800 | 847700 | | 1110600 | |
| 185 | 925/.5 | 415 | 208100 | 1 | 570400 | 779700 | 1033500 | | 1355400 | |
| 240 | 1210/.5 | 500 | 270500 | 1 | 740400 | 1028900 | 1359700 | | 1785700 | |
| 300 | 1527/.5 | 585 | 337500 | 1 | 925400 | 1283100 | 1700800 | | 2220900 | |
| 400 | 2036/.5 | 695 | 459200 | 1 | 1233900 | 1689200 | 2239100 | | 2946300 | |

| | |
|------------------------|-----|
| FR Insulation : | 5% |
| FRLSH /HR Insulation : | 10% |
| HFFR : | 25% |



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

Polycab PVC Insulated, PVC Round Sheathed Multi Core Industrial Flexible Cable conforming to IS 694:1990 with Flexible Bright Annealed Copper Conductor for Voltage Grade upto 1100 Volts

| Nominal Area of Conductor (sq mm) | Number/ Nom. Dia of Conductor (No./dia mm) | Current Carrying Capacity (Amps) | Rate Per 100 Mtrs. Coil | | | |
|-----------------------------------|--|----------------------------------|-------------------------|--------|---------|---------|
| | | | 7 Core | 8 Core | 10 Core | 12 Core |
| 0.5 | 16/.2 | 5 | 5920 | 6900 | 8600 | 10000 |
| 0.75 | 24/.2 | 8 | 8000 | 9900 | 12100 | 14200 |
| 1 | 32/.2 | 13 | 10800 | 12500 | 15200 | 18100 |
| 1.5 | 30/.25 | 17 | 14600 | 16800 | 21000 | 25000 |
| 2.5 | 50/.25 | 24 | 23700 | 27600 | 34100 | 40900 |
| 4 | 56/.3 | 30 | 42100 | 48200 | 61400 | 75300 |
| 6 | 84/0.3 | 37 | 56200 | | | |

| Nominal Area of Conductor (sq mm) | Number/ Nom. Dia of Conductor (No./dia mm) | Current Carrying Capacity (Amps) | Rate Per 100 Mtrs. Coil | | | |
|-----------------------------------|--|----------------------------------|-------------------------|---------|---------|---------|
| | | | 14 Core | 16 Core | 19 Core | 24 Core |
| 0.5 | 16/.2 | 5 | 11700 | 13100 | 15400 | 19600 |
| 0.75 | 24/.2 | 8 | 16500 | 19100 | 22000 | 28000 |
| 1 | 32/.2 | 13 | 21200 | 23900 | 28600 | 35900 |
| 1.5 | 30/.25 | 17 | 29100 | 32800 | 39000 | 49000 |
| 2.5 | 50/.25 | 24 | 47200 | 54300 | 63300 | 79500 |

| Polycab Multi Strand Bare Copper conductor XLPE insulated PVC Sheathed Cables | | | | Rate/ 100m | CCTV CABLES Rate/90m | |
|---|-------------------|-------------------------------|--------------------------------|---|----------------------|-----------------|
| Nominal Area | No/Dia of Strands | Current rating in Air at 40°C | Cu Conductor Unarmoured Cables | Cu Conductor Aluminium Armouring Cables | CCTV Cables 4+1 | CCTV Cables 3+1 |
| mm ² | No/mm | | Rs | Rs | 4000 | 3510 |
| 4 | 56/0.3 | 44 | | | | |
| 6 | 84/0.3 | 55 | 7800 | 10725 | | |
| 10 | 80/0.4 | 75 | 13260 | 18330 | | |
| 16 | 126/0.4 | 103 | 20183 | 23400 | | |
| 25 | 196/0.4 | 126 | 31493 | 35880 | | |
| 35 | 276/0.4 | 152 | 43095 | 48165 | | |
| 50 | 396/0.4 | 189 | 60548 | 66788 | | |
| 70 | 354/0.5 | 240 | 83460 | 91845 | | |
| 95 | 484/0.5 | 297 | 112905 | 117780 | | |
| 120 | 608/0.5 | 346 | 142643 | 148980 | | |
| 150 | 750/0.5 | 390 | 178328 | 186225 | | |
| 185 | 925/0.5 | 460 | 217620 | 224348 | | |
| 240 | 1210/0.5 | 552 | 282653 | 296108 | | |
| 300 | 1527/0.5 | 640 | 352658 | 372450 | | |
| 400 | 2036/0.5 | 753 | 470243 | 493545 | | |
| 500 | 2530/0.5 | 865 | | | | |
| 630 | 3180/0.5 | 1001 | | | | |



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

Polycab FRLS Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:1990 with Flexible Bright Annealed Copper Conductor for Voltage Grade upto 1100 Volts

Polycab PVC Insulated and FRLS Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Cables for Voltage Grade upto 1100 Volts as per IS: 694:1990

| Nominal Area of Conductor (sq mm) | Number/ Nom. Dia of Conductor (No./dia mm) | Current Carrying Capacity (Amps) | Single Core (Rate/100m) | (Rate/100m) | | |
|-----------------------------------|--|----------------------------------|-------------------------|-------------|------------|-----------|
| | | | | Two Core | Three Core | Four Core |
| 0.5 | 16/.2 | 5 | 650 | 2055 | 2850 | 3625 |
| 0.75 | 24/.2 | 8 | 910 | 2760 | 3825 | 4975 |
| 1 | 32/.2 | 13 | 1200 | 3395 | 4730 | 6175 |
| 1.5 | 30/.25 | 17 | 1735 | 4495 | 6320 | 8450 |
| 2.5 | 50/.25 | 24 | 2850 | 7195 | 10100 | 13300 |
| 4 | 56/.3 | 30 | 4525 | 10800 | 15400 | 20300 |
| 6 | 84/.3 | 38 | 6435 | 16200 | 23100 | 30600 |
| 10 | 80/.4 | 52 | 11100 | 27300 | 39600 | 52100 |
| 16 | 126/.4 | 70 | 18100 | 43100 | 62600 | 82500 |
| 25 | 196/.4 | 88 | 28700 | 82500 | 113800 | 149700 |
| 35 | 276/.4 | 110 | 39500 | 112100 | 157600 | 206900 |
| 50 | 396/.4 | 145 | 56400 | 162700 | 224400 | 300400 |
| 70 | 354/.5 | 215 | 78400 | 231700 | 322700 | 419500 |
| 95 | 484/.5 | 260 | 109600 | | | |
| 120 | 608/.5 | 305 | 139800 | | | |
| 150 | 750/.5 | 355 | 174800 | | | |
| 185 | 925/.5 | 415 | 215400 | | | |
| 240 | 1210/.5 | 500 | 279800 | | | |
| 300 | 1527/.5 | 585 | 349600 | | | |
| 400 | 2036/.5 | 695 | 475400 | | | |



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB SOLAR WIRES / CABLES

| Flexible Tinned Copper Conductor Single Core Multistrand, Cross Linked, Zero Halogen Low Smoke Insulation and Cross Linked Low Smoke Sheathing , Heat Resistant upto 120°C and UV Resistant Solar Cables | | Flexible Bare Copper Conductor Multistrand XLPE / PVC Insulated and UV Stabilized PVC Sheathed Single Core and Multicore Solar Cables | |
|--|---------------|---|---------------|
| Size in sq mm | Rate Per 100m | Size in sq mm | Rate Per 100m |
| 1.5 | 5000 | 1.5 | 2890 |
| 2.5 | 6825 | 2.5 | 4590 |
| 4 | 9750 | 4 | 7050 |
| 6 | 13200 | 6 | 10100 |
| 10 | 20700 | 10 | 17400 |
| 16 | 30600 | 16 | 26100 |
| 25 | 47400 | 25 | 40500 |
| 35 | 64600 | 35 | 56100 |
| 50 | 92600 | 50 | 80600 |
| 70 | 128200 | 70 | 111900 |
| 95 | 162800 | 95 | 152300 |
| | | 120 | 189100 |
| | | 150 | 235000 |
| | | 185 | 299800 |
| | | 2 C x 16 | 57300 |
| | | 2 C x 25 | 88500 |

POLYCAB BUILDING MANAGEMENT SYSTEM CABLE (BMS)

Flexible Bare Copper Conductor, PVC Insulated, Cross Laid Up, Overall Aluminium Mylar Tape Shielded along with ATC Drain Wire PVC Outer Sheath BMS Cables (Rate/100m)

| Cores | 0.5 sq.mm (16/.2) | 0.75 sq.mm (24/.2) | 1.0 sq.mm (32/.2) | 1.5 sq.mm (30/.25) | 2.5 sq.mm (50/.25) |
|-------|-------------------|--------------------|-------------------|--------------------|--------------------|
| 2 | 4046 | 4807 | 5762 | 6932 | 11603 |
| 3 | 4807 | 5977 | 7254 | 9272 | 13943 |
| 4 | 5977 | 7361 | 9077 | 11798 | 18135 |
| 5 | 6825 | 8522 | 10920 | 13845 | 21743 |
| 6 | 7683 | 10238 | 12578 | 16185 | 27105 |
| 7 | 8541 | 11505 | 14138 | 18623 | 29543 |
| 10 | 11993 | 15600 | 19695 | 26130 | 41828 |
| 12 | 13845 | 18428 | 23108 | 30713 | 49628 |
| 14 | 15893 | 20963 | 26715 | 35588 | 56940 |
| 16 | 17940 | 24180 | 29250 | 39878 | 65520 |
| 19 | 20573 | 27593 | 35198 | 47190 | 76050 |
| 24 | 25643 | 33540 | 44168 | 59768 | 96038 |

Note : 3% Extra Charges for Drum Packing



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB INDUSTRIAL BRAIDED CABLES

Polycab Annealed Bare Cu Flexible Conductor PVC Insulated, Tinned Cu Braided (Screened) PVC Sheathed Flexible Unarmoured Cables 1100 Volts. (Rate per 100 Mtr)

| Cores | 7/36 | 0.5 sq.mm (16/.2) | 0.75 sq.mm (24/.2) | 1.0 sq.mm (32/.2) | 1.5 sq.mm (30/.25) | 2.5 sq.mm (50/.25) | 4 sq.mm. (56/.3) | 6 sq mm (84/.3) | 10 sq.mm | 16 sq.mm | 25 sq mm | 35 sq.mm. | 50 sq.mm. |
|-------|-------|----------------------|-----------------------|----------------------|-----------------------|-----------------------|---------------------|--------------------|----------|----------|----------|-----------|-----------|
| 2 | 4358 | 5431 | 6981 | 7751 | 9945 | 13748 | 20573 | 26423 | 51700 | 80400 | | | |
| 3 | 5431 | 6689 | 8531 | 9107 | 12090 | 18038 | 26618 | 34223 | 64700 | 101200 | 136400 | 189200 | 247500 |
| 4 | 6689 | 8434 | 10433 | 11603 | 15113 | 23595 | 31395 | 49628 | 92400 | 147800 | 198000 | 250800 | 356400 |
| 5 | 8141 | 10043 | 13943 | 15698 | 18623 | 28178 | | | | | | | |
| 6 | 9214 | 11603 | 15015 | 16575 | 22620 | 33930 | | | | | | | |
| 7 | 9945 | 12383 | 16283 | 18330 | 24278 | 39195 | | | | | | | |
| 8 | 11895 | 14723 | 19208 | 19988 | 27788 | 44363 | | | | | | | |
| 10 | 14138 | 17648 | 23595 | 26325 | 35198 | 51578 | | | | | | | |
| 12 | 16088 | 20280 | 26423 | 29348 | 41048 | 57525 | | | | | | | |
| 14 | 17648 | 22035 | 30225 | 31493 | 48068 | 66885 | | | | | | | |
| 16 | 20378 | 25545 | 33345 | 38318 | 52845 | 76928 | | | | | | | |
| 19 | 23400 | 29250 | 39000 | 45143 | 62790 | 105690 | | | | | | | |
| 24 | 29055 | 36173 | 46313 | 56550 | 77513 | 128603 | | | | | | | |



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB MULTICORE STEEL BRAIDED CABLES (Rate / 100 M)

Flex Bare Copper Conductor,PVC Insulated, Cores Laid Up Together PVC Inner Sheathed, GI Wire Braided (Flexible Armouring), Overall PVC Sheathed Steel Braided Cables.

| Nominal Area of Conductor (sq mm) | Number/ Nom. Dia of Conductor (No./dia mm) | 2 Core | 3 Core | 4 Core | Core | 1.5 sq.mm (30/.25) | 2.5 sq.mm (50/.25) |
|-----------------------------------|--|---------|---------|---------|------|--------------------|--------------------|
| 1.5 | 30/.25 | 8885 | 11742 | 15201 | 5 | 18159 | 27929 |
| 2.5 | 50/.25 | 13228 | 17769 | 22705 | 6 | 21021 | 32672 |
| 4 | 56/.3 | 19145 | 25663 | 33557 | 7 | 23984 | 37511 |
| 6 | 84/.3 | 26943 | 36621 | 47377 | 8 | 27044 | 41254 |
| 10 | 80/.4 | 39675 | 54982 | 72944 | 9 | 29815 | 45799 |
| 16 | 126/.4 | 60009 | 84003 | 110157 | 10 | 32576 | 50836 |
| 25 | 196/.4 | 90714 | 128523 | 169979 | 12 | 38103 | 59918 |
| 35 | 276/.4 | 124372 | 176982 | 233153 | 15 | 46887 | 74325 |
| 50 | 396/.4 | 174712 | 250124 | 330774 | 16 | 49643 | 78967 |
| 70 | 354/.5 | 262563 | 378055 | 501239 | 18 | 55276 | 87851 |
| 95 | 484/.5 | 354364 | 511018 | 678914 | 19 | 58932 | 92190 |
| 120 | 608/.5 | 441225 | 637656 | 847310 | 21 | 64261 | 101378 |
| 150 | 750/.5 | 550400 | 796378 | 1057460 | 24 | 72651 | 114785 |
| 185 | 925/.5 | 684936 | 981557 | 1302254 | | | |
| 240 | 1210/.5 | 876239 | 1271073 | 1689102 | | | |
| 300 | 1527/.5 | 1093196 | 1587330 | 2111273 | | | |

Note : 3% Extra Charges for Drum Packing

Polycab Industrial Speaker Wires

Speaker Wires (Oxygen Free) (Rate per 90 mtr)

| Size 23/36 | Size 40/36 | Size 70/36 |
|------------|------------|------------|
| 1775 | 2810 | 4895 |
| Size 23/38 | Size 40/38 | Size 70/38 |
| 1260 | 2090 | 3290 |

** Flame Retardant, Heat Resistant up to 90°C & Oil Resistant

POLYCAB INDUSTRIAL WELDING CABLES

Polycab Flexible Copper Conductor Welding Cable upto 1100 Volts as per IS-9857 (Rate per 100 mtr)

| Nominal Area of Conductor (sq mm) | Current Carrying Capacity | Conductor Constn. Strands/ Dia in mm | TPR Insulation Rate/100m (Rs) |
|-----------------------------------|---------------------------|--------------------------------------|-------------------------------|
| 16 | 120 | 509/0.2 | 23800 |
| 25 | 160 | 796/0.2 | 34100 |
| 35 | 230 | 1115/0.2 | 46500 |
| 50 | 400 | 703/0.3 | 65900 |
| 70 | 600 | 999/0.3 | 94000 |
| 95 | 700 | 1346/0.3 | 124200 |
| 120 | 1100 | 1699/0.3 | 159400 |



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB ALUMINIUM WIRES & CABLES

| POLYCAB <u>SINGLE CORE</u> PVC INSULATED 1100 VOLTS <u>SOLID</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694 | | POLYCAB <u>SINGLE CORE</u> PVC INSULATED 1100 VOLTS <u>STRANDED</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694 | | POLYCAB PVC INSULATED AND SHEATHED <u>TWIN CORE</u> & <u>THREE CORE</u> FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE <u>STRANDED</u> ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694 | | |
|--|------------|---|------------|---|-------|------------|
| SQ.MM | RATE/ 100M | SQ.MM | RATE/ 100M | NO.OF CORES | SQ.MM | RATE/ 100M |
| 1.5 | 424 | 1.5 | 424 | 2 | 1.5 | 1584 |
| 2.5 | 666 | 2.5 | 666 | 2 | 2.5 | 2240 |
| 4 | 868 | 4 | 979 | 2 | 4 | 3158 |
| 6 | 1311 | 6 | 1352 | 2 | 6 | 4136 |
| 10 | 1957 | 10 | 2028 | 2 | 10 | 6406 |
| POLYCAB <u>SINGLE CORE</u> PVC INSULATED & <u>SHEATHED</u> 1100 VOLTS <u>STRANDED</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694 | | 16 | 2915 | 2 | 16 | 8494 |
| | | 25 | 4550 | 2 | 25 | 11985 |
| | | 35 | 6123 | 2 | 35 | 15364 |
| | | 50 | 8262 | 2 | 50 | 19611 |
| SQ.MM | RATE/ 100M | 70 | 11006 | 2 | 1.5 | 2179 |
| 1.5 | 646 | 95 | 12852 | 3 | 2.5 | 3158 |
| 2.5 | 797 | 120 | 18633 | 3 | 4 | 4469 |
| 4 | 1523 | 150 | 23102 | 3 | 6 | 6214 |
| 6 | 2068 | 185 | 28761 | 3 | 10 | 9150 |
| 10 | 2835 | 240 | 37366 | 3 | 16 | 12418 |
| 16 | 4035 | 300 | 46627 | 3 | 25 | 17432 |
| 25 | 5881 | 400 | 59923 | 3 | 35 | 22557 |
| 35 | 7516 | 500 | 76265 | 3 | 50 | 28761 |
| 50 | 9967 | 630 | 96532 | POLYCAB <u>XLPE</u> INSULATED AND <u>PVC</u> SHEATHED CABLE WITH EACH CORE HAVING STRANDED ALUMINIUM CONDUCTOR SERVICE CABLES GENERALLY CONFORMING TO IS 694. | | |
| POLYCAB PVC INSULATED AND SHEATHED <u>TWIN CORE</u> & <u>THREE CORE</u> FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE <u>SOLID</u> ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694 | | | | NO.OF CORES | SQ.MM | RATE/100M |
| NO.OF CORES | SQ.MM | | RATE/ 100M | 2 | 4 | 2915 |
| 2 | 1.5 | | 1463 | 2 | 6 | 4146 |
| 2 | 2.5 | | 2139 | 2 | 10 | 5165 |
| 2 | 4 | | 2915 | 2 | 16 | 7516 |
| 2 | 6 | | 4035 | | | |
| 2 | 10 | | 6214 | | | |
| 3 | 1.5 | | 2028 | | | |
| 3 | 2.5 | | 3158 | | | |
| 3 | 4 | | 4580 | | | |
| 3 | 6 | | 5770 | | | |
| 3 | 10 | | 8877 | | | |



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB INSTRUMENTATION CABLES

**Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation**

OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

| Type | No. | Size | Rate / mtr | Size | Rate / mtr | Size | Rate / mtr | Size | Rate / mtr | Size | Rate / mtr |
|-------|-----|------|------------|------|------------|------|------------|------|------------|------|------------|
| CORE | 2 | 0.5 | 68 | 0.75 | 78 | 1 | 90 | 1.5 | 107 | 2.5 | 146 |
| CORE | 3 | 0.5 | 79 | 0.75 | 93 | 1 | 117 | 1.5 | 137 | 2.5 | 185 |
| CORE | 4 | 0.5 | 92 | 0.75 | 117 | 1 | 137 | 1.5 | 156 | 2.5 | 234 |
| CORE | 5 | 0.5 | 107 | 0.75 | 127 | 1 | 156 | 1.5 | 185 | 2.5 | 273 |
| CORE | 6 | 0.5 | 117 | 0.75 | 146 | 1 | 176 | 1.5 | 215 | 2.5 | 322 |
| CORE | 7 | 0.5 | 127 | 0.75 | 156 | 1 | 185 | 1.5 | 244 | 2.5 | 361 |
| CORE | 8 | 0.5 | 146 | 0.75 | 176 | 1 | 205 | 1.5 | 273 | 2.5 | 400 |
| CORE | 10 | 0.5 | 166 | 0.75 | 205 | 1 | 263 | 1.5 | 322 | 2.5 | 488 |
| CORE | 12 | 0.5 | 185 | 0.75 | 234 | 1 | 293 | 1.5 | 380 | 2.5 | 585 |
| CORE | 14 | 0.5 | 205 | 0.75 | 263 | 1 | 332 | 1.5 | 429 | 2.5 | 653 |
| CORE | 16 | 0.5 | 234 | 0.75 | 293 | 1 | 371 | 1.5 | 488 | 2.5 | 741 |
| CORE | 19 | 0.5 | 263 | 0.75 | 332 | 1 | 429 | 1.5 | 556 | 2.5 | 848 |
| CORE | 24 | 0.5 | 312 | 0.75 | 410 | 1 | 527 | 1.5 | 692 | 2.5 | 1063 |
| PAIR | 1 | 0.5 | 68 | 0.75 | 79 | 1 | 88 | 1.5 | 107 | 2.5 | 146 |
| PAIR | 2 | 0.5 | 107 | 0.75 | 127 | 1 | 146 | 1.5 | 176 | 2.5 | 244 |
| PAIR | 3 | 0.5 | 127 | 0.75 | 146 | 1 | 176 | 1.5 | 224 | 2.5 | 332 |
| PAIR | 4 | 0.5 | 146 | 0.75 | 176 | 1 | 224 | 1.5 | 283 | 2.5 | 410 |
| PAIR | 5 | 0.5 | 166 | 0.75 | 205 | 1 | 263 | 1.5 | 341 | 2.5 | 497 |
| PAIR | 6 | 0.5 | 185 | 0.75 | 244 | 1 | 302 | 1.5 | 390 | 2.5 | 585 |
| PAIR | 7 | 0.5 | 205 | 0.75 | 273 | 1 | 341 | 1.5 | 439 | 2.5 | 663 |
| PAIR | 8 | 0.5 | 244 | 0.75 | 302 | 1 | 390 | 1.5 | 507 | 2.5 | 761 |
| PAIR | 10 | 0.5 | 283 | 0.75 | 371 | 1 | 468 | 1.5 | 605 | 2.5 | 926 |
| PAIR | 12 | 0.5 | 322 | 0.75 | 419 | 1 | 536 | 1.5 | 712 | 2.5 | 1073 |
| PAIR | 14 | 0.5 | 361 | 0.75 | 478 | 1 | 614 | 1.5 | 809 | 2.5 | 1238 |
| PAIR | 16 | 0.5 | 410 | 0.75 | 536 | 1 | 683 | 1.5 | 917 | 2.5 | 1414 |
| PAIR | 19 | 0.5 | 458 | 0.75 | 624 | 1 | 809 | 1.5 | 1063 | 2.5 | 1638 |
| PAIR | 24 | 0.5 | 566 | 0.75 | 770 | 1 | 995 | 1.5 | 1336 | 2.5 | 2057 |
| TRIAD | 1 | 0.5 | 81 | 0.75 | 98 | 1 | 117 | 1.5 | 137 | 2.5 | 185 |
| QUAD | 1 | 0.5 | 93 | 0.75 | 117 | 1 | 137 | 1.5 | 156 | 2.5 | 224 |



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad/Quad laid up together with Al Inner sheathed Mylar/Drain Wire PVC Inner Sheathed Unrmoured PVC Outer Sheathed Instrumentation Cable.

OVERALL SHIELDED - UNARMoured INSTRUMENTATION CABLES

| Type | No. | Size | Rate / mtr | Size | Rate / mtr | Size | Rate / mtr | Size | Rate / mtr | Size | Rate / mtr |
|-------|-----|------|------------|------|------------|------|------------|------|------------|------|------------|
| PAIR | 1 | 0.5 | 40 | 0.75 | 49 | 1 | 59 | 1.5 | 70 | 2.5 | 98 |
| PAIR | 2 | 0.5 | 62 | 0.75 | 79 | 1 | 98 | 1.5 | 137 | 2.5 | 185 |
| PAIR | 3 | 0.5 | 82 | 0.75 | 107 | 1 | 137 | 1.5 | 176 | 2.5 | 263 |
| PAIR | 4 | 0.5 | 98 | 0.75 | 137 | 1 | 176 | 1.5 | 224 | 2.5 | 341 |
| PAIR | 5 | 0.5 | 127 | 0.75 | 166 | 1 | 263 | 1.5 | 273 | 2.5 | 419 |
| PAIR | 6 | 0.5 | 146 | 0.75 | 185 | 1 | 244 | 1.5 | 332 | 2.5 | 497 |
| PAIR | 7 | 0.5 | 156 | 0.75 | 215 | 1 | 273 | 1.5 | 371 | 2.5 | 575 |
| PAIR | 8 | 0.5 | 176 | 0.75 | 234 | 1 | 322 | 1.5 | 419 | 2.5 | 653 |
| PAIR | 10 | 0.5 | 215 | 0.75 | 302 | 1 | 390 | 1.5 | 527 | 2.5 | 819 |
| PAIR | 12 | 0.5 | 254 | 0.75 | 351 | 1 | 458 | 1.5 | 624 | 2.5 | 965 |
| PAIR | 14 | 0.5 | 283 | 0.75 | 400 | 1 | 527 | 1.5 | 712 | 2.5 | 1112 |
| PAIR | 16 | 0.5 | 332 | 0.75 | 449 | 1 | 605 | 1.5 | 819 | 2.5 | 1268 |
| PAIR | 19 | 0.5 | 380 | 0.75 | 536 | 1 | 702 | 1.5 | 956 | 2.5 | 1492 |
| PAIR | 24 | 0.5 | 468 | 0.75 | 663 | 1 | 878 | 1.5 | 1199 | 2.5 | 1892 |
| TRIAD | 1 | 0.5 | 50 | 0.75 | 61 | 1 | 75 | 1.5 | 96 | 2.5 | 146 |
| QUAD | 1 | 0.5 | 59 | 0.75 | 73 | 1 | 94 | 1.5 | 127 | 2.5 | 185 |

**POLYCAB WIRES PVT. LTD.**

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

| Type | No. | Size | Rate / mtr | Size | Rate / mtr | Size | Rate / mtr | Size | Rate / mtr | Size | Rate / mtr |
|------|-----|------|------------|------|------------|------|------------|------|------------|------|------------|
| PAIR | 2 | 0.5 | 127 | 0.75 | 146 | 1 | 166 | 1.5 | 195 | 2.5 | 254 |
| PAIR | 3 | 0.5 | 156 | 0.75 | 176 | 1 | 205 | 1.5 | 254 | 2.5 | 351 |
| PAIR | 4 | 0.5 | 185 | 0.75 | 215 | 1 | 254 | 1.5 | 312 | 2.5 | 439 |
| PAIR | 5 | 0.5 | 224 | 0.75 | 263 | 1 | 312 | 1.5 | 371 | 2.5 | 527 |
| PAIR | 6 | 0.5 | 254 | 0.75 | 302 | 1 | 361 | 1.5 | 439 | 2.5 | 624 |
| PAIR | 7 | 0.5 | 283 | 0.75 | 332 | 1 | 400 | 1.5 | 488 | 2.5 | 712 |
| PAIR | 8 | 0.5 | 312 | 0.75 | 380 | 1 | 458 | 1.5 | 566 | 2.5 | 800 |
| PAIR | 10 | 0.5 | 380 | 0.75 | 458 | 1 | 556 | 1.5 | 692 | 2.5 | 995 |
| PAIR | 12 | 0.5 | 439 | 0.75 | 527 | 1 | 644 | 1.5 | 800 | 2.5 | 1170 |
| PAIR | 14 | 0.5 | 497 | 0.75 | 605 | 1 | 741 | 1.5 | 917 | 2.5 | 1336 |
| PAIR | 16 | 0.5 | 556 | 0.75 | 683 | 1 | 829 | 1.5 | 1034 | 2.5 | 1521 |
| PAIR | 19 | 0.5 | 634 | 0.75 | 780 | 1 | 965 | 1.5 | 1209 | 2.5 | 1784 |
| PAIR | 24 | 0.5 | 800 | 0.75 | 975 | 1 | 1209 | 1.5 | 1531 | 2.5 | 2243 |



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed Unarmoured PVC Outer Sheathed Instrumentation Cable.

INDIVIDUAL & OVERALL SHIEDED - UNARMoured INSTRUMENTATION CABLES

| Type | No. | Size | Rate / mtr | Size | Rate / mtr | Size | Rate / mtr | Size | Rate / mtr | Size | Rate / mtr |
|------|-----|------|------------|------|------------|------|------------|------|------------|------|------------|
| PAIR | 2 | 0.5 | 84 | 0.75 | 98 | 1 | 117 | 1.5 | 146 | 2.5 | 205 |
| PAIR | 3 | 0.5 | 107 | 0.75 | 137 | 1 | 166 | 1.5 | 205 | 2.5 | 293 |
| PAIR | 4 | 0.5 | 137 | 0.75 | 166 | 1 | 205 | 1.5 | 263 | 2.5 | 380 |
| PAIR | 5 | 0.5 | 166 | 0.75 | 205 | 1 | 254 | 1.5 | 322 | 2.5 | 468 |
| PAIR | 6 | 0.5 | 195 | 0.75 | 244 | 1 | 302 | 1.5 | 380 | 2.5 | 556 |
| PAIR | 7 | 0.5 | 224 | 0.75 | 273 | 1 | 341 | 1.5 | 429 | 2.5 | 634 |
| PAIR | 8 | 0.5 | 254 | 0.75 | 312 | 1 | 390 | 1.5 | 497 | 2.5 | 731 |
| PAIR | 10 | 0.5 | 312 | 0.75 | 390 | 1 | 488 | 1.5 | 614 | 2.5 | 897 |
| PAIR | 12 | 0.5 | 361 | 0.75 | 458 | 1 | 566 | 1.5 | 722 | 2.5 | 1073 |
| PAIR | 14 | 0.5 | 429 | 0.75 | 527 | 1 | 663 | 1.5 | 839 | 2.5 | 1238 |
| PAIR | 16 | 0.5 | 478 | 0.75 | 595 | 1 | 741 | 1.5 | 956 | 2.5 | 1414 |
| PAIR | 19 | 0.5 | 556 | 0.75 | 702 | 1 | 878 | 1.5 | 1121 | 2.5 | 1667 |
| PAIR | 24 | 0.5 | 702 | 0.75 | 878 | 1 | 1102 | 1.5 | 1414 | 2.5 | 2096 |



POLYCAB RUBBER CABLES

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED , PC TAPE , PCP OUTERSHEATHED ELASTOMERIC RUBBER CABLE (Rate Per Mtr)

| Size Sq.mm | 1 Core | 2 Core | 3 Core | 4 Core |
|------------|----------------|----------------|----------------|----------------|
| 1.5 | 65 | 169 | 193 | 243 |
| 2.5 | 87 | 224 | 264 | 337 |
| 4 | 121 | 319 | 376 | 484 |
| 6 | 192 | 484 | 581 | 778 |
| 10 | 287 | 733 | 888 | 1157 |
| 16 | 412 | 1027 | 1282 | 1675 |
| 25 | 610 | -- | 1971 | 2556 |
| 35 | 820 | -- | 2600 | 3385 |
| 50 | 1059 | -- | 3336 | 4350 |
| 70 | 1575 | -- | 4910 | 6454 |
| 95 | 2085 | -- | 6508 | 8536 |
| 120 | 2579 | -- | 7995 | 10530 |
| 150 | 3161 | -- | 9788 | 12900 |
| 185 | 3870 | -- | 11975 | 15824 |
| 240 | 4975 | -- | 15484 | 20468 |
| 300 | 6176 | -- | 19374 | 25617 |
| | 6 Core | 7 Core | 8 Core | 10 Core |
| 1.5 | 331 | 410 | 496 | 623 |
| 2.5 | 501 | 608 | 711 | 849 |
| | 12 Core | 16 Core | 19 Core | |
| 1.5 | 714 | 924 | 1088 | |
| 2.5 | 1011 | 1294 | 1558 | |



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

| SIZE | 5 PAIR | 10 PAIR | 20 PAIR | 50 PAIR | 100 PAIR | 200 PAIR |
|------|--------|---------|---------|---------|----------|----------|
| 0.5 | 57 | 94 | 166 | 371 | 731 | 1463 |
| | | | | | | |

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED,G.S.TAPE ARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

| SIZE | 5 PAIR | 10 PAIR | 20 PAIR | 50 PAIR | 100 PAIR | 200 PAIR |
|------|--------|---------|---------|---------|----------|----------|
| 0.5 | 107 | 146 | 224 | 468 | 829 | 1560 |
| | | | | | | |