



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT (FR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 VOLTS

Size (sq.mm.)	FR					
	90 Mtrs.	Coils Per Box	180 Mtrs. (Box Packing)	Coils Per Box	300/200 Mtrs.	Coils Per Box
0.75	810	28			2700	10
1	1055	24	2110	12	3515	8
1.5	1570	16	3140	10	5235	6
2.5	2525	12	5050	6	8415	4
4	3735	8	7470	4	8300	4
6	5540	6	11080	3	12310	3
10	9750	1			21670	1
16	15600	1			34665	1

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES – FLAME RETARDANT LOW SMOKE (FRLSH) /FLAME RETARDANT ZERO HALOGEN (FRZH) / LOW SMOKE ZERO HALOGEN (LSZH) / HALOGEN FREE FLAME RETARDANT (HFFR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 VOLTS

Size (sq.mm.)	FRLS				FRZH/LSZH/HFFR	
	180 Mtrs. (Box Packing)	Coils Per Box	300/200 Mtrs.	Coils Per Box	300/200 Mtrs.	Coils Per Box
0.75			2850	10	3190	10
1	2185	12	3650	8	3940	8
1.5	3305	10	5510	6	6105	6
2.5	5315	6	8855	4	10040	4
4	7850	4	8720	4	9750	4
6	11600	3	12890	3	14235	3
10			22815	1	25060	1
16			36565	1	39975	1

Notes

1. Excise Duty, VAT, Entry Tax, Octroi/ LBT and any other tax/levy will be charged extra, as per actuals.
2. This Price List is subject to change without notice.
3. As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB INDUSTRIAL JELLY FLOODED COAXIAL CABLES

Polycab Gas Injected Physical Polyethylene Foam Insulation with Laminated Aluminium Tape and Aluminium Wire Braid, Jelly Flooded PVC Black Jacketed Industrial Coaxial Cables.

Size	100m Unarmoured	305m Unarmoured	1000m Armoured
RG - 59	1870	5215	76050
RG - 6	2430	7410	78975
RG - 11	5040	15405	121875
RG-6 CCS	1540	4710	71175
RG-11 CCS	3090	9420	

POLYCAB LAN (COMPUTER) CABLES

Polycab 4 Pair Unshielded Twisted Pair (UTP) LAN (Computer) Cables

Polycab 4 Pair Shielded Twisted Pair (STP) LAN (Computer) Cables

	Unarmoured Rate per 305 m	Armoured- Rate per 100m	STP- Rate per 305m	Armoured – Rate per 100m
CAT 5 E	8735	6810	11325	8095
CAT 6	10415	7805	13205	9265



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB INDUSTRIAL TELEPHONE (SWITCHBOARD)CABLES

Polycab High Conductivity Solid Annealed Bare Copper industrial Telephone (Switchboard) Cables with High Density Polyethylene Insulation, Paired, Polyester and Sheathed with High Oxygen Index, Fire Retardant, PVC Compound, Grey Outer Sheath generally conforming ITD Specification

No. of Pairs & Size			
	0.4 mm	0.5 mm	Master Packing
1 Pair	650	780	20
2 Pair	1035	1365	20
3 Pair	1520	1990	16
4 Pair	1950	2615	12
5 Pair	2440	3265	8
10 Pair		6240	1
20 Pair		12000	1
50 Pair		33200	1
100 Pair		63400	1

ARMOURED TELEPHONE CABLES

No. of Pairs	Rate / 100m (0.5sqmm)	Master Packing 0.5 mm
2 Pair	4485	0 Drums/Coils as required
5 Pair	7400	0 Drums/Coils as required
10 Pair	11100	0 Drums/Coils as required
15 Pair	15200	0 Drums/Coils as required
20 Pair	18700	0 Drums/Coils as required
50 Pair	44900	0 Drums/Coils as required
100 Pair	82200	0 Drums/Coils as required

POLYCAB IND. 3C FLAT SUBMERSIBLE CABLES

Polycab PVC Insulated and PVC Sheathed Industrial 3 Core Flat Submersible Cable with Bare Bunched Copper Conductor for Submersible Pump Motors with Voltage Grade upto 1100 Volts as per IS:694/1990

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Cables (No./dia mm)	Rate per 100m (Rs)
1.5	22/.3	6500
2.5	36/.3	10100
4	56/.3	14900

Polycab Special PVC Insulated & PVC Sheathed Industrial 3 Core Flat Submersible Cables with Bare Bunched Copper Conductor for Submersible Pump Motors with Voltage Grade Upto 1100 Volts generally conforming to IS 694/1990.

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Cables (No./dia mm)	Rate per 100m (Rs)
6	84/0.3	21900
10	80/0.4	37400
16	126/0.4	59900
25	196/0.4	95900
35	276/.4	134400
50	396/.4	192300
70	354/.5	267600
95		345800
120		442100
150		550900

Notes :

1) The above cables are supplied in 500/1000m drums.

2) Polycab Three Core Flat Submersible Cables

Insulated & Sheathed with XLPE can be supplied at

the same rates as given above.



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

Polycab PVC Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:1990 with Flexible Bright Annealed Copper Conductor for Voltage Grade upto 1100 Volts

Polycab PVC Insulated and PVC Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Cables for Voltage Grade upto 1100 Volts as per IS: 694:1990

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	(Rate/100m)							
			Single Core	Packing	2 Core	3 Core	4 Core	2 - 4 Core Packing	5 Core	6 Core
0.5	16/.2	5	625	25	1970	2650	3410	4	4330	5130
0.75	24/.2	8	880	25	2625	3570	4435	4	6055	7400
1	32/.2	13	1150	20	3130	4310	5625	4	8000	9350
1.5	30/.25	17	1670	16	4235	5940	7880	4	10400	12700
2.5	50/.25	24	2750	12	6750	9500	12600	3	17100	20700
4	56/.3	30	4310	8	10000	14200	18600	1	26000	32800
6	84/.3	38	6240	6	15000	21600	28100	--	40300	48200
10	80/.4	52	10800	1	25500	36800	47900	--	68500	--
16	126/.4	70	17500	1	40700	58600	77100	--	106800	--
25	196/.4	88	27600	1	77000	104700	137700	--	181100	--
35	276/.4	110	38100	1	105100	145000	190400	--	250100	--
50	396/.4	145	54400	1	152200	206600	276500	--	362600	--
70	354/.5	215	75600	1	216800	297100	386300		505800	
95	484/.5	260	105800	1	292800	407100	537500		698000	
120	608/.5	305	135000	1	370700	516600	693000		906600	
150	750/.5	355	168900	1	462600	641800	847700		1110600	
185	925/.5	415	208100	1	570400	779700	1033500		1355400	
240	1210/.5	500	270500	1	740400	1028900	1359700		1785700	
300	1527/.5	585	337500	1	925400	1283100	1700800		2220900	
400	2036/.5	695	459200	1	1233900	1689200	2239100		2946300	

FR Insulation :	5%
FRLSH /HR Insulation :	10%
HFFR :	25%



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

Polycab PVC Insulated, PVC Round Sheathed Multi Core Industrial Flexible Cable conforming to IS 694:1990 with Flexible Bright Annealed Copper Conductor for Voltage Grade upto 1100 Volts

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			7 Core	8 Core	10 Core	12 Core
0.5	16/.2	5	5920	6900	8600	10000
0.75	24/.2	8	8000	9900	12100	14200
1	32/.2	13	10800	12500	15200	18100
1.5	30/.25	17	14600	16800	21000	25000
2.5	50/.25	24	23700	27600	34100	40900
4	56/.3	30	42100	48200	61400	75300
6	84/0.3	37	56200			

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			14 Core	16 Core	19 Core	24 Core
0.5	16/.2	5	11700	13100	15400	19600
0.75	24/.2	8	16500	19100	22000	28000
1	32/.2	13	21200	23900	28600	35900
1.5	30/.25	17	29100	32800	39000	49000
2.5	50/.25	24	47200	54300	63300	79500

Polycab Multi Strand Bare Copper conductor XLPE insulated PVC Sheathed Cables				Rate/ 100m	CCTV CABLES Rate/90m	
Nominal Area	No/Dia of Strands	Current rating in Air at 40°C	Cu Conductor Unarmoured Cables	Cu Conductor Aluminium Armouring Cables	CCTV Cables 4+1	CCTV Cables 3+1
mm ²	No/mm		Rs	Rs	4000	3510
4	56/0.3	44				
6	84/0.3	55	7800	10725		
10	80/0.4	75	13260	18330		
16	126/0.4	103	20183	23400		
25	196/0.4	126	31493	35880		
35	276/0.4	152	43095	48165		
50	396/0.4	189	60548	66788		
70	354/0.5	240	83460	91845		
95	484/0.5	297	112905	117780		
120	608/0.5	346	142643	148980		
150	750/0.5	390	178328	186225		
185	925/0.5	460	217620	224348		
240	1210/0.5	552	282653	296108		
300	1527/0.5	640	352658	372450		
400	2036/0.5	753	470243	493545		
500	2530/0.5	865				
630	3180/0.5	1001				



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

Polycab FRLS Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:1990 with Flexible Bright Annealed Copper Conductor for Voltage Grade upto 1100 Volts

Polycab PVC Insulated and FRLS Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Cables for Voltage Grade upto 1100 Volts as per IS: 694:1990

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Single Core (Rate/100m)	(Rate/100m)		
				Two Core	Three Core	Four Core
0.5	16/.2	5	650	2055	2850	3625
0.75	24/.2	8	910	2760	3825	4975
1	32/.2	13	1200	3395	4730	6175
1.5	30/.25	17	1735	4495	6320	8450
2.5	50/.25	24	2850	7195	10100	13300
4	56/.3	30	4525	10800	15400	20300
6	84/.3	38	6435	16200	23100	30600
10	80/.4	52	11100	27300	39600	52100
16	126/.4	70	18100	43100	62600	82500
25	196/.4	88	28700	82500	113800	149700
35	276/.4	110	39500	112100	157600	206900
50	396/.4	145	56400	162700	224400	300400
70	354/.5	215	78400	231700	322700	419500
95	484/.5	260	109600			
120	608/.5	305	139800			
150	750/.5	355	174800			
185	925/.5	415	215400			
240	1210/.5	500	279800			
300	1527/.5	585	349600			
400	2036/.5	695	475400			



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB SOLAR WIRES / CABLES

Flexible Tinned Copper Conductor Single Core Multistrand, Cross Linked, Zero Halogen Low Smoke Insulation and Cross Linked Low Smoke Sheathing , Heat Resistant upto 120°C and UV Resistant Solar Cables		Flexible Bare Copper Conductor Multistrand XLPE / PVC Insulated and UV Stabilized PVC Sheathed Single Core and Multicore Solar Cables	
Size in sq mm	Rate Per 100m	Size in sq mm	Rate Per 100m
1.5	5000	1.5	2890
2.5	6825	2.5	4590
4	9750	4	7050
6	13200	6	10100
10	20700	10	17400
16	30600	16	26100
25	47400	25	40500
35	64600	35	56100
50	92600	50	80600
70	128200	70	111900
95	162800	95	152300
		120	189100
		150	235000
		185	299800
		2 C x 16	57300
		2 C x 25	88500

POLYCAB BUILDING MANAGEMENT SYSTEM CABLE (BMS)

Flexible Bare Copper Conductor, PVC Insulated, Cross Laid Up, Overall Aluminium Mylar Tape Shielded along with ATC Drain Wire PVC Outer Sheath BMS Cables (Rate/100m)

Cores	0.5 sq.mm (16/.2)	0.75 sq.mm (24/.2)	1.0 sq.mm (32/.2)	1.5 sq.mm (30/.25)	2.5 sq.mm (50/.25)
2	4046	4807	5762	6932	11603
3	4807	5977	7254	9272	13943
4	5977	7361	9077	11798	18135
5	6825	8522	10920	13845	21743
6	7683	10238	12578	16185	27105
7	8541	11505	14138	18623	29543
10	11993	15600	19695	26130	41828
12	13845	18428	23108	30713	49628
14	15893	20963	26715	35588	56940
16	17940	24180	29250	39878	65520
19	20573	27593	35198	47190	76050
24	25643	33540	44168	59768	96038

Note : 3% Extra Charges for Drum Packing



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB INDUSTRIAL BRAIDED CABLES

Polycab Annealed Bare Cu Flexible Conductor PVC Insulated, Tinned Cu Braided (Screened) PVC Sheathed Flexible Unarmoured Cables 1100 Volts. (Rate per 100 Mtr)

Cores	7/36	0.5 sq.mm (16/.2)	0.75 sq.mm (24/.2)	1.0 sq.mm (32/.2)	1.5 sq.mm (30/.25)	2.5 sq.mm (50/.25)	4 sq.mm. (56/.3)	6 sq mm (84/.3)	10 sq.mm	16 sq.mm	25 sq mm	35 sq.mm.	50 sq.mm.
2	4358	5431	6981	7751	9945	13748	20573	26423	51700	80400			
3	5431	6689	8531	9107	12090	18038	26618	34223	64700	101200	136400	189200	247500
4	6689	8434	10433	11603	15113	23595	31395	49628	92400	147800	198000	250800	356400
5	8141	10043	13943	15698	18623	28178							
6	9214	11603	15015	16575	22620	33930							
7	9945	12383	16283	18330	24278	39195							
8	11895	14723	19208	19988	27788	44363							
10	14138	17648	23595	26325	35198	51578							
12	16088	20280	26423	29348	41048	57525							
14	17648	22035	30225	31493	48068	66885							
16	20378	25545	33345	38318	52845	76928							
19	23400	29250	39000	45143	62790	105690							
24	29055	36173	46313	56550	77513	128603							



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB MULTICORE STEEL BRAIDED CABLES (Rate / 100 M)

Flex Bare Copper Conductor,PVC Insulated, Cores Laid Up Together PVC Inner Sheathed, GI Wire Braided (Flexible Armouring), Overall PVC Sheathed Steel Braided Cables.

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	2 Core	3 Core	4 Core	Core	1.5 sq.mm (30/.25)	2.5 sq.mm (50/.25)
1.5	30/.25	8885	11742	15201	5	18159	27929
2.5	50/.25	13228	17769	22705	6	21021	32672
4	56/.3	19145	25663	33557	7	23984	37511
6	84/.3	26943	36621	47377	8	27044	41254
10	80/.4	39675	54982	72944	9	29815	45799
16	126/.4	60009	84003	110157	10	32576	50836
25	196/.4	90714	128523	169979	12	38103	59918
35	276/.4	124372	176982	233153	15	46887	74325
50	396/.4	174712	250124	330774	16	49643	78967
70	354/.5	262563	378055	501239	18	55276	87851
95	484/.5	354364	511018	678914	19	58932	92190
120	608/.5	441225	637656	847310	21	64261	101378
150	750/.5	550400	796378	1057460	24	72651	114785
185	925/.5	684936	981557	1302254			
240	1210/.5	876239	1271073	1689102			
300	1527/.5	1093196	1587330	2111273			

Note : 3% Extra Charges for Drum Packing

Polycab Industrial Speaker Wires

Speaker Wires (Oxygen Free) (Rate per 90 mtr)

Size 23/36	Size 40/36	Size 70/36
1775	2810	4895
Size 23/38	Size 40/38	Size 70/38
1260	2090	3290

** Flame Retardant, Heat Resistant up to 90°C & Oil Resistant

POLYCAB INDUSTRIAL WELDING CABLES

Polycab Flexible Copper Conductor Welding Cable upto 1100 Volts as per IS-9857 (Rate per 100 mtr)

Nominal Area of Conductor (sq mm)	Current Carrying Capacity	Conductor Constn. Strands/ Dia in mm	TPR Insulation Rate/100m (Rs)
16	120	509/0.2	23800
25	160	796/0.2	34100
35	230	1115/0.2	46500
50	400	703/0.3	65900
70	600	999/0.3	94000
95	700	1346/0.3	124200
120	1100	1699/0.3	159400



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB ALUMINIUM WIRES & CABLES

POLYCAB <u>SINGLE CORE</u> PVC INSULATED 1100 VOLTS <u>SOLID</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694		POLYCAB <u>SINGLE CORE</u> PVC INSULATED 1100 VOLTS <u>STRANDED</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694		POLYCAB PVC INSULATED AND SHEATHED <u>TWIN CORE</u> & <u>THREE CORE</u> FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE <u>STRANDED</u> ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694		
SQ.MM	RATE/ 100M	SQ.MM	RATE/ 100M	NO.OF CORES	SQ.MM	RATE/ 100M
1.5	424	1.5	424	2	1.5	1584
2.5	666	2.5	666	2	2.5	2240
4	868	4	979	2	4	3158
6	1311	6	1352	2	6	4136
10	1957	10	2028	2	10	6406
POLYCAB <u>SINGLE CORE</u> PVC INSULATED & <u>SHEATHED</u> 1100 VOLTS <u>STRANDED</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694		16	2915	2	16	8494
		25	4550	2	25	11985
		35	6123	2	35	15364
		50	8262	2	50	19611
70	11006	2	70	2179	3158	
95	12852	3	95	4469	6214	
120	18633	3	120	9150	12418	
150	23102	3	150	17432	22557	
185	28761	3	185	28761		
240	37366	3	240			
300	46627	3	300			
400	59923	3	400			
500	76265	3	500			
630	96532	3	630			
POLYCAB PVC INSULATED AND SHEATHED <u>TWIN CORE</u> & <u>THREE CORE</u> FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE <u>SOLID</u> ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694				POLYCAB <u>XLPE</u> INSULATED AND <u>PVC</u> SHEATHED CABLE WITH EACH CORE HAVING STRANDED ALUMINIUM CONDUCTOR SERVICE CABLES GENERALLY CONFORMING TO IS 694.		
NO.OF CORES	SQ.MM		RATE/ 100M	NO.OF CORES	SQ.MM	RATE/100M
2	1.5		1463	2	4	2915
2	2.5		2139	2	6	4146
2	4		2915	2	10	5165
2	6		4035	2	16	7516
2	10		6214			
3	1.5		2028			
3	2.5		3158			
3	4		4580			
3	6		5770			
3	10		8877			



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB INSTRUMENTATION CABLES

**Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation**

OVERALL SHIELDED - ARMoured INSTRUMENTATIION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
CORE	2	0.5	68	0.75	78	1	90	1.5	107	2.5	146
CORE	3	0.5	79	0.75	93	1	117	1.5	137	2.5	185
CORE	4	0.5	92	0.75	117	1	137	1.5	156	2.5	234
CORE	5	0.5	107	0.75	127	1	156	1.5	185	2.5	273
CORE	6	0.5	117	0.75	146	1	176	1.5	215	2.5	322
CORE	7	0.5	127	0.75	156	1	185	1.5	244	2.5	361
CORE	8	0.5	146	0.75	176	1	205	1.5	273	2.5	400
CORE	10	0.5	166	0.75	205	1	263	1.5	322	2.5	488
CORE	12	0.5	185	0.75	234	1	293	1.5	380	2.5	585
CORE	14	0.5	205	0.75	263	1	332	1.5	429	2.5	653
CORE	16	0.5	234	0.75	293	1	371	1.5	488	2.5	741
CORE	19	0.5	263	0.75	332	1	429	1.5	556	2.5	848
CORE	24	0.5	312	0.75	410	1	527	1.5	692	2.5	1063
PAIR	1	0.5	68	0.75	79	1	88	1.5	107	2.5	146
PAIR	2	0.5	107	0.75	127	1	146	1.5	176	2.5	244
PAIR	3	0.5	127	0.75	146	1	176	1.5	224	2.5	332
PAIR	4	0.5	146	0.75	176	1	224	1.5	283	2.5	410
PAIR	5	0.5	166	0.75	205	1	263	1.5	341	2.5	497
PAIR	6	0.5	185	0.75	244	1	302	1.5	390	2.5	585
PAIR	7	0.5	205	0.75	273	1	341	1.5	439	2.5	663
PAIR	8	0.5	244	0.75	302	1	390	1.5	507	2.5	761
PAIR	10	0.5	283	0.75	371	1	468	1.5	605	2.5	926
PAIR	12	0.5	322	0.75	419	1	536	1.5	712	2.5	1073
PAIR	14	0.5	361	0.75	478	1	614	1.5	809	2.5	1238
PAIR	16	0.5	410	0.75	536	1	683	1.5	917	2.5	1414
PAIR	19	0.5	458	0.75	624	1	809	1.5	1063	2.5	1638
PAIR	24	0.5	566	0.75	770	1	995	1.5	1336	2.5	2057
TRIAD	1	0.5	81	0.75	98	1	117	1.5	137	2.5	185
QUAD	1	0.5	93	0.75	117	1	137	1.5	156	2.5	224



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad/Quad laid up together with Al Inner sheathed Mylar/Drain Wire PVC Inner Sheathed Unrmoured PVC Outer Sheathed Instrumentation Cable.

OVERALL SHIELDED - UNARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	1	0.5	40	0.75	49	1	59	1.5	70	2.5	98
PAIR	2	0.5	62	0.75	79	1	98	1.5	137	2.5	185
PAIR	3	0.5	82	0.75	107	1	137	1.5	176	2.5	263
PAIR	4	0.5	98	0.75	137	1	176	1.5	224	2.5	341
PAIR	5	0.5	127	0.75	166	1	263	1.5	273	2.5	419
PAIR	6	0.5	146	0.75	185	1	244	1.5	332	2.5	497
PAIR	7	0.5	156	0.75	215	1	273	1.5	371	2.5	575
PAIR	8	0.5	176	0.75	234	1	322	1.5	419	2.5	653
PAIR	10	0.5	215	0.75	302	1	390	1.5	527	2.5	819
PAIR	12	0.5	254	0.75	351	1	458	1.5	624	2.5	965
PAIR	14	0.5	283	0.75	400	1	527	1.5	712	2.5	1112
PAIR	16	0.5	332	0.75	449	1	605	1.5	819	2.5	1268
PAIR	19	0.5	380	0.75	536	1	702	1.5	956	2.5	1492
PAIR	24	0.5	468	0.75	663	1	878	1.5	1199	2.5	1892
TRIAD	1	0.5	50	0.75	61	1	75	1.5	96	2.5	146
QUAD	1	0.5	59	0.75	73	1	94	1.5	127	2.5	185

**POLYCAB WIRES PVT. LTD.**

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	127	0.75	146	1	166	1.5	195	2.5	254
PAIR	3	0.5	156	0.75	176	1	205	1.5	254	2.5	351
PAIR	4	0.5	185	0.75	215	1	254	1.5	312	2.5	439
PAIR	5	0.5	224	0.75	263	1	312	1.5	371	2.5	527
PAIR	6	0.5	254	0.75	302	1	361	1.5	439	2.5	624
PAIR	7	0.5	283	0.75	332	1	400	1.5	488	2.5	712
PAIR	8	0.5	312	0.75	380	1	458	1.5	566	2.5	800
PAIR	10	0.5	380	0.75	458	1	556	1.5	692	2.5	995
PAIR	12	0.5	439	0.75	527	1	644	1.5	800	2.5	1170
PAIR	14	0.5	497	0.75	605	1	741	1.5	917	2.5	1336
PAIR	16	0.5	556	0.75	683	1	829	1.5	1034	2.5	1521
PAIR	19	0.5	634	0.75	780	1	965	1.5	1209	2.5	1784
PAIR	24	0.5	800	0.75	975	1	1209	1.5	1531	2.5	2243



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed Unarmoured PVC Outer Sheathed Instrumentation Cable.

INDIVIDUAL & OVERALL SHIELED - UNARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	84	0.75	98	1	117	1.5	146	2.5	205
PAIR	3	0.5	107	0.75	137	1	166	1.5	205	2.5	293
PAIR	4	0.5	137	0.75	166	1	205	1.5	263	2.5	380
PAIR	5	0.5	166	0.75	205	1	254	1.5	322	2.5	468
PAIR	6	0.5	195	0.75	244	1	302	1.5	380	2.5	556
PAIR	7	0.5	224	0.75	273	1	341	1.5	429	2.5	634
PAIR	8	0.5	254	0.75	312	1	390	1.5	497	2.5	731
PAIR	10	0.5	312	0.75	390	1	488	1.5	614	2.5	897
PAIR	12	0.5	361	0.75	458	1	566	1.5	722	2.5	1073
PAIR	14	0.5	429	0.75	527	1	663	1.5	839	2.5	1238
PAIR	16	0.5	478	0.75	595	1	741	1.5	956	2.5	1414
PAIR	19	0.5	556	0.75	702	1	878	1.5	1121	2.5	1667
PAIR	24	0.5	702	0.75	878	1	1102	1.5	1414	2.5	2096



POLYCAB RUBBER CABLES

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED , PC TAPE , PCP OUTERSHEATHED ELASTOMERIC RUBBER CABLE (Rate Per Mtr)

Size Sq.mm	1 Core	2 Core	3 Core	4 Core
1.5	65	169	193	243
2.5	87	224	264	337
4	121	319	376	484
6	192	484	581	778
10	287	733	888	1157
16	412	1027	1282	1675
25	610	--	1971	2556
35	820	--	2600	3385
50	1059	--	3336	4350
70	1575	--	4910	6454
95	2085	--	6508	8536
120	2579	--	7995	10530
150	3161	--	9788	12900
185	3870	--	11975	15824
240	4975	--	15484	20468
300	6176	--	19374	25617
	6 Core	7 Core	8 Core	10 Core
1.5	331	410	496	623
2.5	501	608	711	849
	12 Core	16 Core	19 Core	
1.5	714	924	1088	
2.5	1011	1294	1558	



POLYCAB WIRES PVT. LTD.

LDC LIST PRICE NO 02 /2015-16 effective 25th June 2015

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	57	94	166	371	731	1463

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED,G.S.TAPE ARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	107	146	224	468	829	1560